



E. J. CADY & COMPANY
135 SOUTH WHEELING ROAD
WHEELING, ILLINOIS 60090 - 4807 U.S.A.

Purchase on-line 24 hours a day at: www.ejcady.com

Phone: (847) 537-2239
 Fax: (847) 537-1766
 Email: ejcady@ejcady.com
 Website: www.ejcady.com



CERTIFIED STEEL GAGE BLOCKS

We distribute but do not manufacture the following gage blocks:

Standard features include: Square, Steel, Grade 0, Traceable to N.I.S.T.

Available Sizes: .050"	REQUEST
.100"	REQUEST
.200"	REQUEST
.250"	REQUEST

**Most other specific grades and sizes are available upon request.*

PORTABLE MICROMETERS

POCKET MICROMETERS

We distribute but do not manufacture the following pocket micrometers:

Quick Mini Model	REQUEST
Digital display, English/Metric readings	

Available ranges: 0 - 1/2" / 0 - 12 mm
 0 - 1" / 0 - 25 mm

P-60 Model	REQUEST
-------------------------	---------

Available dial graduations: .001"
 .01 mm

HAND MICROMETERS

Standard features include: 5/8" anvils, Range: 0 - 5/16", 7 - 9 p.s.i. (1" and 2 1/2" Models only)

Standard features include: 5/8" anvils, Range: 0 - .300" (approx.), 7 - 9 p.s.i. (6" Model only)

Available throat depths: 1"	\$450.00
2 1/2"	550.00
6"	675.00

Available dial graduations: Dial HA (.001")
 Dial HM (.01 mm)

Optional additional features: Range: 0 - .400" (1" and 2 1/2" Models only)	\$125.00
Anvil sets - Up to 1" diameter	150.00
Anvil sets - 1+ " to 2" diameter	180.00

PRICES ARE SUBJECT TO CHANGE WITHOUT NOTICE.
 RETURNED INSTRUMENTS WILL BE ASSESSED A 25% RESTOCKING CHARGE.
 F.O.B. WHEELING, ILLINOIS, U.S.A.

Rev. 07/10



E. J. CADY & COMPANY
135 SOUTH WHEELING ROAD
WHEELING, ILLINOIS 60090 - 4807 U.S.A.

Purchase on-line 24 hours a day at: www.ejcady.com

Phone: (847) 537-2239
 Fax: (847) 537-1766
 Email: ejcady@ejcady.com
 Website: www.ejcady.com



ANALOG (DIAL) BENCH MICROMETERS

M MODEL

Standard features include: 5/8" anvils, Range: 0 - 5/16", 7 - 9 p.s.i., Accuracy: $\pm .0002"$ - $.0003"$
 and/or $\pm .00508$ mm - $.00762$ mm

Available throat depths: 4"	\$895.00
12"	1100.00
18"	1225.00

Available dial graduations: Dial A (.001")
 Dial B (.0005")
 Dial M (.01 mm)
 Dial MA (.001" and .01 mm)

Optional additional features: Range: 0 - 1/2"	\$125.00
Anvil sets - Up to 1" diameter	150.00
Anvil sets - 1" to 2" diameter	180.00
Micrometer clamps.....	15.00/set
Electric motor - 9 RPMs, 4" throat only	575.00

DW MODEL

Standard features include: 5/8" anvils, Range: 0 - 1/2", 5.8+ p.s.i., Accuracy: $\pm .0002"$ - $.0003"$
 and/or $\pm .00508$ mm - $.00762$ mm

Available throat depths: 4"	\$1010.00
7"	1135.00
12"	1280.00
18"	1435.00

Available dial graduations: Dial A (.001")
 Dial B (.0005")
 Dial M (.01 mm)
 Dial MA (.001" and .01 mm)

Optional additional features: Vernier to give readings in .0001" - Dial A only.....	\$125.00
Range: 0 - 1"	200.00
Anvil sets - Up to 1" diameter	150.00
Anvil sets - 1" to 2" diameter	180.00
Micrometer clamps.....	15.00/set
Delayed Action	225.00
Pneumatic operation - 12" and 18" throats only	615.00
Electric motor - 9 RPMs, 4" throat	575.00
Electric motor - 9 RPMs, 7" throat	610.00

PRICES ARE SUBJECT TO CHANGE WITHOUT NOTICE.
 RETURNED INSTRUMENTS WILL BE ASSESSED A 25% RESTOCKING CHARGE.
 F.O.B. WHEELING, ILLINOIS, U.S.A.

Rev. 07/10



E. J. CADY & COMPANY
135 SOUTH WHEELING ROAD
WHEELING, ILLINOIS 60090 - 4807 U.S.A.

Purchase on-line 24 hours a day at: www.ejcady.com

Phone: (847) 537-2239
 Fax: (847) 537-1766
 Email: ejcady@ejcady.com
 Website: www.ejcady.com



OTHER SPECIALIZED ANALOG (DIAL) BENCH MICROMETERS

DW14 MODEL - Roofing Industry

Standard features include: 5/8" upper anvil, 2" lower anvil, Range: 0 - 1/2", 2.8 p.s.i.,
 Accuracy: ± .0002" - .0003" and ± .00508 mm - .00762 mm

Available throat depth: 4" \$1100.00

Available dial graduations: Dial A (.001")
 Dial B (.0005")
 Dial M (.01 mm)
 Dial MA (.001" and .01 mm)

Optional additional feature: Micrometer clamps..... \$15.00/set

MC MODEL - Non Rigid Plastic Industry

Standard features include: .250" upper anvil, Range: 0 - 5/16", 3.6 p.s.i.

Available throat depth: 4" \$925.00

Available dial graduations: Dial A (.001")
 Dial B (.0005")
 Dial M (.01 mm)
 Dial MA (.001" and .01 mm)

TT MODEL

Standard features include: 5/8" anvils, Range: 0 - .050"

Available throat depth: 4" \$1550.00

Available dial graduations: Dial 10A (.0001")
 Dial 10M (.001 mm)



E. J. CADY & COMPANY
135 SOUTH WHEELING ROAD
WHEELING, ILLINOIS 60090 - 4807 U.S.A.

Purchase on-line 24 hours a day at: www.ejcady.com

Phone: (847) 537-2239
 Fax: (847) 537-1766
 Email: ejcady@ejcady.com
 Website: www.ejcady.com



LITHOGRAPHIC ANALOG (DIAL) BENCH MICROMETERS

DWL MODEL

Standard features include: 9/16" upper anvil, 5/8" lower anvil, Range: 0 - 1/2", 7.2 p.s.i.,
 Accuracy: $\pm .0002"$ - $.0003"$ and/or $\pm .00508$ mm - $.00762$ mm

Available throat depths: 4"	\$1085.00
7"	1210.00
12"	1370.00
18"	1530.00

Available dial graduations: Dial B (.0005")
 Dial M (.01 mm)
 Dial MA (.001" and .01 mm)

Optional additional features: Micrometer clamps	\$15.00/set
Delayed Action	225.00
Pneumatic operation - 12" and 18" throats only	615.00
Electric motor - 9 RPMs, 4" throat.....	575.00
Electric motor - 9 RPMs, 7" throat.....	610.00

LITHOGRAPHIC DIGITAL BENCH MICROMETERS

DDWL MODEL

Standard features include: 9/16" upper anvil, 5/8" lower anvil, 7.2- p.s.i., English and metric units,
 Range: 0 - .500"/0 - 12.7 mm, Resolution: .0001" and .001 mm,
 Accuracy: $\pm .0002"$ - $.0003"$ and $\pm .00508$ mm - $.00762$ mm, RS-232
 interface port

Available throat depths: 4"	\$1775.00
7"	1925.00
12"	2075.00
18"	2225.00

Available operating methods: Battery and electric
 Electric only

Optional additional features: Micrometer clamps	\$15.00/set
Delayed Action	225.00
Pneumatic operation - 12" and 18" throats only	615.00



E. J. CADY & COMPANY
135 SOUTH WHEELING ROAD
WHEELING, ILLINOIS 60090 - 4807 U.S.A.

Purchase on-line 24 hours a day at: www.ejcady.com

Phone: (847) 537-2239
 Fax: (847) 537-1766
 Email: ejcady@ejcady.com
 Website: www.ejcady.com



DIGITAL BENCH MICROMETERS

DDW MODEL

Standard features include: 5/8" anvils, 5.8+ p.s.i., Range: 0 - .500"/0 - 12.7 mm, English/metric units, Resolution: .0001" and .001 mm, Accuracy: ± .0002" - .0003" and ± .00508 mm - .00762 mm, RS-232 interface port

Available throat depths: 4"	\$1700.00
7"	1850.00
12"	2000.00
18"	2150.00

Available operating methods: Battery and electric
 Electric only

Optional additional features: Range: 0 - 1"	\$200.00
Anvil sets - Up to 1" diameter	150.00
Anvil sets - 1+ " to 2" diameter	180.00
Micrometer clamps.....	15.00/set
Delayed Action	225.00
Pneumatic operation - 12" and 18" throats only	615.00

DDW-T MODEL

Standard features include: Meets TAPPI T-411, 0.63" anvils, 7.3 p.s.i., Range: 0 - .400"/0 - 10.16 mm, English/metric units, Resolution: .0001" and .001 mm, Accuracy: .001 mm or 1% of sample thickness for most materials .010" or larger*, RS-232 interface port

***NOTE:** In some cases, it may be necessary to utilize a calibration chart for smaller thicknesses to meet the specified accuracy.

Available throat depth: 4"	\$3300.00
----------------------------------	-----------

Available operating method: Electric only

Optional additional features: Micrometer clamps	15.00/set
---	-----------